







LT9201

SPECS

| Product # | LT9201 |
|--------------|--------------|
| Wattage | 6W |
| Voltage | 12/24V AC/DC |
| ССТ | 2700-6000K |
| Lumen | 580lm |
| Beam Spread | 52° |
| CRI | ≥85Ra |
| Working Temp | -40°C ~40°C |

| | | _ | |
|---|---|---|--|
| _ | u | | |
| | | | |

- Engineered for outdoor lighting applications
- Advanced drive and LED solutions
- Shockproof internal structure
- IP67 weatherproof and water-resistant
- Top quality electronic components

| Inner Box | 5.04"(L)x4.96"(W)x4.02"(H) 12.8(L)*12.6(W)*10.2(H)cm |
|------------------------|---|
| PCs/Inner Box | 1 PC |
| Master Carton | 20.7"(L)x15.8"(W)x8.7"(H) 52.6(L)*40(W)*22(H)cm |
| PCs/Master Carton | 24 PC |
| Product Weights | 0.87 LBS / 0.39 KG |
| Net Weights | 20.9 LBS / 9.48 KG |
| Gross Weights | 23.8 LBS / 10.80 KG |
| | |

MATERIALS

WARRANTY

Aluminum

3 years warranty

LENS

Frosted PC

FINISH

ORB

INSTALLATION



