CABLE | Specification Sheet

LANDSCAPE LIGHTING DIRECT BURIAL CABLE

PRODUCT FEATURES

Material	100% Virgin PVC + 100% Full Copper
Color	Black
AWG	10/12/14/16
Conductors	2
Use temperature	-20℃ to 60℃
Use Voltage	30V-150V
Useage	Low-voltage landscape lighting
Standards	UL Subj 1493 cUL standards C22 .2 35 , CSA class 5834-01

SPECIFICATIONS

MODEL	LENGTH	WIRE SIZE	NOM.OVERALL DIA (INCH)	GROSS WEIGHT (LB/MFT)
LLC10100	100FT	10/2	0.205X0.405	10.34LBS/ 4.70KG
LLC10250	250FT	10/2	0.205X0.405	27.47LBS/12.48KG
LLC10500	500FT	10/2	0.205X0.405	53.86LBS/24 .48KG
LLC12100	100FT	12/2	0.186X0.370	7.57LBS/ 3.44KG
LLC12250	250FT	12/2	0.186X0.370	19. 10LBS/ 8.68KG
LLC12500	500FT	12/2	0.186X0.370	36.96LBS/16.80KG
LLC14100	100FT	14/2	0.166X0.341	4.36LBS/10.98KG
LLC14250	250FT	14/2	0.166X0.341	11.22LBS/ 5.10KG
LLC14500	500FT	14/2	0.166X0.341	21.78LBS/ 9.90KG
LLC16100	100FT	16/2	0.156X0.307	3.08LBS/ 1.40KG
LLC16250	250FT	16/2	0.156X0.307	8.45LBS/ 3.84KG
LLC16500	500FT	16/2	0.156X0.307	16.46LBS/ 7.48KG

Lutou Technology Co., Ltd
Shenzhen | Huizhou | Taizhou L.A.
www.lutou-tech.com | info@lutou-tech.com | +86-755-28716871

Lutou Tech Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.