

# **PRODUCT FEATURES**

| Lamp Type     | MR16<br>(Sold Separately)                                  |
|---------------|--|
| Wattage       | UP to 50W  |
| Voltage       | 9 – 17V AC/DC  |
| Lead wire     | Pre-stripped SVT 2x18 AWG Gauge, L=72"                     |
| IP Rating     | IP65   |
| Lens Material | Clear glass Lens   |
| Housing       | Solid Brass + Nylon  |
| Finish        | AB Antique Bronze / GM Gun Metal Black /<br>MB Matte Black |
| Dimensions    | 4.9"DIA x 6.1"H  |



# **ORDERING INFORMATION**

| CATAGORY   | MODEL   | FINISH             | LAMP | ACCESSORIES   |
|------------|---------|--------------------|------|---|
| WELL LIGHT | LT2204C | AB Antique Bronze  | 4W   | LT403A MR16 Louvre  |
|            |         | GM Gun Metal Black | 5W   |   |
|            |         | MB Matte Black     | 6W   |   |
|            |         |                    | 7W   |   |
|            |         |                    | 8W   |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      |   |
|            |         |                    |      | Please consult for details on other optional accessories. |





## **SPECIFICATIONS**

## HOUSING CONSTRUCTION:

Solid brass.

### FINISH:

AB Antique Bronze. GM Gun Metal Black. MB Matte Black.

### LENS:

Clear glass lens.

#### LED LAMP:

MR16 LED Lamp(sold separately).


## LAMP BRACKET ANGLE ADJUSTABLE


Yes.

## **ELECTRICAL:**

Input voltage range 9 - 17V AC/DC. Low voltage transformer required to operate (sold separately).

## **DIMENSIONS**





LT2204C

WIRING:

Prewired with a 72" pigtail of 18/2 cable.



PROFESSIONAL OUTDOOR LIGHTING